Range Specifications

AGROMULCH[®] Gold

| | Trailed | | | | |
|------------------------------------------------------------------|---------|---------|---------|---------|---------|
| Model | 4,00 m | 5,00 m | 6,00 m | 7,00 m | 8,00 m |
| Power req. (HP) | 200-260 | 240-300 | 280-360 | 350-450 | 400-520 |
| Number of tines | 13 | 17 | 19 | 25 | 27 |
| Weight in Shear-Bolt security with Cage roller Ø526 (≈ kg) | 5 570 | 6 070 | 6 380 | 9 100 | 9 320 |
| Weight in Non-Stop security with Cage roller Ø526 (≈ kg) | 6 780 | 7 516 | 7 870 | 9 335 | 9 630 |

AGRISEM® 535 rue Pierre Levasseur - CS 60263 44158 ANCENIS - FRANCE

T. +33 (0) 2 51 14 14 40 F. + 33 (0) 2 40 96 32 36

www.agrisem.com agrisem@agrisem.com



| Your Dealer: | |
|--------------|--|
| | |
| | |
| | |



AGROMULCH[®] trailed

AGROMULCH®



The AGROMULCH[®] has developed for the hard cultivating with non-stop spring security.

The working depth is to 5 to 25 cm. It is possible to mulch the surface residues with 335 mm wing ploughshare but also without winged ploughshare up to 25 cm deep for pseudo-ploughing in healthy conditions.

This machine ensures a very intensive soil work «structure and unpack».

AGROMULCH[®] can be used along the year to scalping the crop regrowth or for pseudo-ploughing in healthy conditions.

AGROMULCH[®] Gold trailed



Depth control wheels



Spring security



» Release at the tip: +500 kg of pressure » Important clearance for the release » Non-stop spring security

Criss-crossing of the wings



» Superficial stubble-breaker after harvest » Destruction of the crops

Homogeneous work



» Intensive mixing of the crops » Creation of a regular mulch » Perfect levelling-out

Tine rear each transport wheel To work without roller in wet condition

Levelling-out



» Irreprochable surface

» Improved soil structure

» Facilitated gestion of the crops

Working depth



» Without the wings: work at 25cm deep

» With the wings: work at 5 to 15cm deep

Exclusivity

Retracted point blade PATENTED

By replacing the tines by blades, it becomes a soil loosener

» 1 machine for 2 functions

» Use all year long

» Easy to replace