

# **STRIPCAT**



THE STRI-TILL SPECIALIST  
Strip-Till  
Drill  
Fertilise



# STRIP-TILL

## WHAT IS STRIP-TILL ?

Strip-till is a conservation system which uses minimum tillage. It combines the soil-drying and warming benefits of conventional tillage with the soil-protecting advantages of no-till by disturbing only the portion of the soil that is to contain the seed row.

Strip-tilling works by creating a pathway and seedbed through the previous crop residue. Unlike other techniques, it moves the residue between the tilled rows to protect the soil.

The strip-till makes a strip from 10 to 20cm wide and 5 to 30cm deep.

Strip-till time will depend on soil type, like in conventional tillage:

- heavy land (>20% clay):  
autumn strip-till
- light soil:  
spring strip-till



## STRIP TILLING OFFERS THE SAFETY OF CONVENTIONAL TILLAGE AND THE SAVINGS AND AGRONOMIC ADVANTAGES OF NO-TILL

- ✓ Reduced fuel consumption up to 50L/ha
- ✓ Reduced fertiliser rate up to 30% thanks to localisation
- ✓ Improved water efficiency
- ✓ Improved soil warming compared to direct seeding
- ✓ More even stand
- ✓ Faster establishment
- ✓ Improved root system
- ✓ Easier management of cover crop

## GROW MORE WITH LESS! WHICH CROPS...



# ROW UNIT

- 1 Parallel linkage with adjustable down pressure
- 2 Gauge wheels
- 3 Non-stop hydraulic tripping (option)
- 4 Depth setting without tool
- 5 Independent birm builders with variable angle and width
- 6 Packing system with pneumatic down pressure



- 1 DISC OPENER Open the line and cut the mulch
- 2 TRASH WHEEL Clean the trash to create a clean strip (patented SUNCO sabertooth)
- 3 SHANK (6 models available) Work the soil and place dry and/or liquid fertiliser
- 4 BIRM BUILDERS Maintain the soil in place to create a nice birm
- 5 PACKING WHEEL (2 models available)

Pack the strip and crumble the soil to create an homogeneous seedbed



Finger wheel



Farmflex  
wheel



# BUILT TO WORK & LAST IN THE TOUGHEST CONDITIONS



## **New birm builders**

allow an adjustment of the angle, width, and position of the discs without tools. This system of shims allows repositioning to give a wider or narrower strip, and a row spacing down to 45cm.




## **Tool free**

adjustment of the working depth



## **Pneumatic springs**

allow adjustment of both down pressure on the parallel linkage and lighter or harder packing on the rear.



## **Floating SUNCO trash managers**

adjustable from the cab

## **Patented teeth and chisel spikes**

Wear points adapted to both liquid and solid fertilisers. Interchangeable points allow a flexible and low cost approach to maintenance. Now available with tungsten carbide tip.



## ADDITIONAL EQUIPMENT

### **OPTIONAL**

#### ■ **Non-Stop security system**



#### ■ **Floating trash wheels**



#### ■ **Dual disc kit & shank holder**



#### ■ **Carbide point**



## FERTILISATION KITS


### ■ Tank

Available capacity  
700, 1100, 1200,  
1500, 1850  
(2 products)  
or 2000L



### ■ LiquidXConnect

- 2 models, 15 or 75l/mn
- Fittings, couplings
- GPS and on/off switch
- Software for IOS or Android



### ■ Liquid fertilisation kit

- WILGER Ball Flow Indicators
- 1 set of nozzle at the user's choice
- connections
- assembly on StripCat



### ■ Solid fertilisation kit

- Simple (63mm) or double outlet (2x32mm hose)
- manifold Ø 100mm
- air release (1 per hose)
- assembly on



### ■ Double injection Kit

For solid or slurry kit



### ■ Slurry Injection kit

- Hexacut head mont
- Teeth equipment



## SEEDING UNITS

Bogie seeding system tailored to rape or cover crop seeding.

Can be mounted with packing unit or without to leave a smooth birm fall tillage.


### ■ Single row seeding unit

Centered or offset seeding. Packing wheel measurements: 300x100mm



### ■ Twin row seeding unit

Seed in the edges of the strip for dual cover crops or rape seed: spacing from 17 to 23cm. Packing wheel measurements: 300x50mm



- Twin row (no bogie)  
Allow you to seed while leaving a smooth birm (autumn work).



## OPTIONAL EQUIPMENT

### ■ Heavy duty markers



### ■ Hopper access foot-bridge



### ■ Pneumatic Brakes



### ■ Rear linkage Cat 3-4 T



### ■ Hopper

Please consult us for further information



### ■ Lights



## OPTIONAL FRAME

### ■ Three point hitch mounted folding frame

From 3 to 9m, 2,9m on the road

### ■ Trailed kit Up to 6m



### Lift Assist Up to 9m



### ■ Trailed Folding frame Over 6m





# THERE IS A STRIPCAT FOR EVERY FARMER

Rigid, vertical, or trailed folding frame allows many configurations. Now the Stripcat is available from 4 to 16 rows and from 45 to 80 cm spacing, while maintaining a road width of 3 metres.



16 rows 76cm, trailed for grain maize and sunflower



12 rows 45cm with seeding units for rape seeding



6 rows 50/80cm for oilseedrape and maize



12 rows 75cm for slurry injections



24 rows 45cm with seeding units



12 rows 50cm for maize seeding after rye silage

535 rue Pierre Levasseur - CS 60263  
44158 ANCENIS - FRANCE

T. +33 (0) 2 51 14 14 40

[www.agrisem.com](http://www.agrisem.com)  
[agrisem@agrisem.com](mailto:agrisem@agrisem.com)

#YellowTeam



Your Dealer: