

T-BOSS



All the **technicity** for a **seeder of precision**



The assets of the no-till tines seeder

- Clean furrow, clean of plant remains
- «Clod clearer» effect to clear rocks and blocks
- Micro-fissuration of the tine = drainage and rooting
- No smoothing
- Mineralisation effect around the row
- Only one wearing part
- Limited traction needed



Adjustable frame

The T-BOSS benefits from an adjustable frame, with the position of the seeding elements on 4 rows varying from 18,5 to 25 cm. The conception allows, in addition to being scalable, optimisation of spaces and the extraction of the machine.

At the front, the machine is stabilised by 3 wheels situated in a way to avoid risks of stuffing.



PNEUMATIC SUPPORT PRESSURISATION

- Easy pressure adjustment.
- Smooth shock absorption without jolts or juddering.

DECOMPRESSOR

- Available as an option, eliminates the risk of bouncing out of the furrow.
- Allows higher seed and fertiliser flow rates.

GROUND-FOLLOWING PARALLELOGRAM

- Consistent ground following with a constant tine and uniform depth.
- Lateral rigidity and row precision ensured by the main linkage arm fitted with a double-row bearing.

SEED DROP

- Adjustable seed placement behind the coulter heel.
- Second drop (optional), shallower placement (small seeds).

«LOW-DISTURBANCE» NARROW COULTER

- Point angle and shape designed to limit soil disturbance and earth projections.
- Tungsten carbide blades with sharpening.
- Removable, interchangeable coulter.
- Windged version for wide distribution (optional).

EASYDEPTH

- Simple and quick individual depth adjustment.
- Off position: lifted wheel enabling operation in extreme condition.

FARM-FLEX W CONTROL AND PRESS WHEEL

- Concentrated pressure on each side of the row to promote closing.
- 110 mm width of stability and ground following.
- Scraper for sticky conditions.



Features

	Mounted foldable								
Working width (≈ m)	4,50	4,80	6		6,40	7,20	7,50	8,00	
Transport width (≈ m)	3,00	3,00	3,00	3,00	3,00	3,00	3,00	3,00	3,00
Number of row	24	24	24	32	32	32	40	32	40
Row spacing (cm)	18,75	20	25	18,75	20	22,5	18,75	25	20
Weight in standard version (≈ kg)	2 485	2 485	2 545	3 035	3 050	3 050	3 560	3 100	3 610
Min-max power (ch)	145 - 200	145 - 200	150 - 230	165 - 250	165 - 250	170 - 260	190 - 280	175 - 270	190 - 280
Hitch	3-point linkage, Cat.3								
Number of hydraulic distributors	1hydraulic distributor : folding								
Support wheels	3 wheels 23x10,50-12								


Accessories



FarmFlex "W" wheel



Spider finger wheels



2-row tine coulter



Low-Disturbance coulter



Spreader coulter



535 rue Pierre Levasseur - CS 60263
44158 ANCENIS - FRANCE

T. +33 (0) 2 51 14 14 40

www.agrisem.com
agrisem@agrisem.com

#YellowTeam



Your dealer :